


NX20-508RS4

Features

- Full HD Display
- 8Ch. Recording (max. 15fps/ch)
- Support AHD, TVI, CVI, 960H, IP
- 8 Channel BNC Input
- Support POS
- 2HDD
- Network Function - DDNS, DHCP, UPNP
- Smartphone Viewer Support (Android/iPhone/iPad)



Specifications

NX20-508RS4	
VIDEO	
Input	8 BNC
Input Resolution	4K(8MP), 5MP, 4MP, 3MP, 2MP
Output	1 HDMI, 1VGA, 1 D-SUB
Output Resolution	UHD, QHD, FHD, SXGA, XGA
RECORDING	
Speed	2MP : 30fps/ch 3MP,4MP : 15fps/ch 5MP : 10fps/ch 4K(8MP) : 8fps/ch
Compression	H.265, H.264
Resolution	4K(8MP), 5MP, 4MP, 3MP, 2MP, 960H
PLAYBACK	
Speed	2MP : 208 fps 3MP: 146 fps 4MP: 117fps 5MP: 86fps 4K(8MP): 52fps
Resolution	4K(8MP), 5MP, 4MP, 3MP, 2MP, 960H
AUDIO	
Input	8 RCA
Output	1 HDMI, 1 RCA
INTERFACE	
Sensor In / Out	8 / 1 - NC / NO
USB	2 x USB 2.0
PTZ / Keyboard	RS485 - Terminal Block
ATM / POS	Ethernet POS

NETWORK	
Interface	Ethernet 10/100/1G
Compression	H.264, H.265
Speed	8fps(4K0), 10fps(5MP), 30fps(2MP)
Resolution	Normal 2MP, REC Bypass Max. 4K
STORAGE	
Primary	2 HDD
SYSTEM	
OS	Embedded Linux (Built-in Flash Memory)
Pre / Post-Alarm	5sec / 5sec~5min
Recording Mode	Continuous, Event, Schedule
Data Search	Calendar, Multi Day / Time, Event, Go to Time
Backup Interface	USB, Network
Backup Type	Video (RMS, AVI), Capture (JPEG), Lot List, Setup Data
Alarm Action	Buzzer, PTZ Preset, E-mail, Relay, Event Popup, Push
User	15 Users (Admin, User1 ~ User14)
Network Viewer	CMS, Web Viewer, etc CCTV Smart Viewer (iOS, Android)
ONVIF	ONVIF Profile T
GENERAL	
Dimensions	430 x 270 x 86 mm (WxDxH)
Weight(w/o HDD)	4kg (8.8 lbs)
Temp / Humidity	5 ~ 40°C / 10% ~80%
Power Supply	12V / 5A
Power Consumption	60 Watts